

Industrial / Spectacles / 506 UP HYBRID

## 506 UP Hybrid - In/Out G65

Code: 506UG.63.08.00

Date: 27-09-23 1/2

**Frame mark (EU)**

506U U 166 FT CE

**Lens mark (EU)**

2C-1.4/5-1.4 U 1 FT KN CE

**Gasket mark (EU)**

506U U 166 FT CE / U 175 -F 506UG U 166 FT CE

**Frame technology**

Hybrid, Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal

**Conditions of use**

Standard brightness, Low brightness, Indoor - Outdoor

**Lens technology**

Anti-Scratch + Anti-Fog (KN - Vanguard PLUS), In/Out G65

**Lens color**

Clear

**Lens material**

Polycarbonate

**Frame color**

Black/Green

**Standards**

EN166, EN170, EN172

**Scale number**

(2C-1.4), (5-1.4)

**Mechanical resistance**

Low energy impact (F)

**Optional requirements**

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

**Optical class**

Optical class (1)

**Weight**

38g

>> <https://www.univetsafety.com/en/products/safety/spectacles/506-up-hybrid/506-up-hybrid-in-out-g65/>



01.

LENS WITH ANTI-FOG AND ANTI-  
SCRATCH ULTRA PERFORMING  
VANGUARD PLUS TREATMENT

02.

TEMPLES ADJUSTABLE IN  
INCLINATION

03.

SOFT-RUBBER GASKET  
for a gentle support on the face

04.

PANORAMIC AND WRAPAROUND  
LENS

for a better side protection

05.

ADJUSTABLE ELASTIC BAND

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

#### HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - [info@univetsafety.com](mailto:info@univetsafety.com)  
VAT. IT02506570163