

DOC. NO.	REVISION	ISSUE	DATE
QF/RD/05	01	00	31-10-2019



TOWER HARNESS

Ref. No. PN 56



TESTED AS PER EN 358:1999, EN 813:2008 & EN 361:2002



TECHNICAL DATA SHEET

DESIGN

- One dorsal attachment D-Ring for fall arrest
- One front attachment D-Ring at chest for fall arrest
- Two lateral D-Rings at waist for positioning
- One ventral D-Ring at waist level for rope access
- Adjustable shoulder & leg straps
- Adjustable waist belt
- Comfort pads on leg straps for extended comfort

WEIGHT

2240 gm \pm 10 gm

WEBBING

Material	:	Polyester
Width	:	44 \pm 1 mm
Minimum Breaking Strength	:	25 kN

STITCHING THREAD

Material	:	High Tenacity Polyester
----------	---	-------------------------

METAL COMPONENTS

Material	:	High Strength Steel
Plating	:	Zinc Plated
Finish	:	Deburred & Polished

VITAL TEST COMPLIANCE

Static Strength	:	Each attachment element tested at 15 kN or 1,530 kgf for 3 Minutes
Dynamic Performance	:	Free fall from 4 meters height donned to a test dummy weighing 100 kg at each attachment element.